

# SUPER PLAST

Emulsion Paint

## Description:

SUPER PLAST is based on polyvinyl acetate emulsion. It is high quality interior emulsion paint easy to apply. Exhibits good flow and leveling. Exhibits excellent hiding power and high spreading rate.

## Recommended Use:

Suitable for use on interior surfaces including concrete, cement, gypsum and plaster.

## Specification Data:

<b>Specific Gravity</b>	1.45 + 0.05 KG/L
<b>Viscosity</b>	110 + 5 poise
<b>Solid by Volume</b>	39 + 3 %
<b>Finish</b>	Matt
<b>Coverage</b>	10 + 2 m <sup>2</sup> /Kg
<b>Drying Time (for touch)</b>	30 min. at 25° C
<b>Drying Time (for recoat)</b>	2 hours at 25° C
<b>Thinner</b>	Water
<b>Thinning</b>	25% first coat – 10% second coat
<b>Washability</b>	More than 1000 cycle
<b>Mode of Application</b>	Brush or spray
<b>Storage</b>	2 years from date of production

## Surface Preparation:

The surfaces should be dry, clean and free from contaminants such as grease, oil, dust ...etc., which can result in adhesion of the paint to the surface.

New Surfaces

Apply one coat Sealer 1800 on cement, concrete and gypsum surfaces then two Latex Putty coats. Use two or three coats Bortoplast Emulsion

## Repainting:

Cement surfaces should be cleaned with water and soap, rinse thoroughly with water insure the surface is free from all contaminants then let the surface to dry well for flakes or defect painted surface use a sanding paper to release it then apply previous item.