

UNI 6060

Semi-Gloss Emulsion Paint

Description:

UNI 6060 is an outstanding top quality waterborne based on the best quality acrylic copolymer for new and old exterior facades, designed to withstand all weather changes have the advantage of easy application, can be repainted the same day. Has a very low odor level, excellent adhesion, property with primed surface, with extremely high hiding power and does not yellow with age. Available in white color and a wide range of colors by use a dispensing machine.

Recommended Use:

UNI 6060 is ideal for exterior walls and ceilings constructed from concrete, plaster, cement rendering, blocks, asbestos, plaster board, wall paper and wood.

Specification Data:

Specific Gravity	1.4 + 0.05 KG/L
Viscosity	125 + 5 KU
Solid by Volume	55 %+1
Finish	Matt
Coverage	9 - 12m ² /Kg
Drying Time (for touch)	40 min. at 25° C
Drying Time (for recoat)	2 hours at 25° C
Thinner	Water
Thinning	10% first coat – 20% second coat
Lead content %	0%
Washability	ASTM 1600 gr only)
Mode of Application	Brush or spray
Storage	2 years from date of production
Wet film thickness (WFT)	70Mm according to the percent of dilution by water
Dry film thickness (DFT)	55 Mm
Bottles	3L&10L

Surface Preparation:

The surfaces should be dry, clean and free from contaminates such as grease, oil, dust, which can result in poor adhesion of the paint to the surface. Use a suitable solvent for cleaning old flaking paint or poorly bound surfaces must be removed completely. to get finished surface free from runs, drops, gidges, wave, laps, brush marks, and variations in colors.

Storage:

2 years in the principle containers. keep out from direct sun.