

## UNI GLOSS

Glossy Synthetic Paint

### Description:

UNI GLOSS is a high quality glossy synthetic paint manufactured from the best quality materials.

### Advantages:

UNI GLOSS is made to withstand different weather conditions with high yellowing resistance, perfect coverage ability, excellent durability and hiding power.

### Specification Data:

<b>Thinner</b>	White spirit or turpentine
<b>Viscosity</b>	11.45min at 25 C on cup ford (for white)
<b>Drying Method</b>	Oxidization and evaporation
<b>Precautions</b>	Not to be used under 10 ° C
<b>Drying Time (for touch)</b>	3 – 4 hours at 25 ° C
<b>Drying Time (hard dry)</b>	16 – 20 hours at 10 ° C
<b>Coverage</b>	10 – 12 m <sup>2</sup> /L – depending on layer thickness
<b>Color</b>	White – various colors
<b>Finish</b>	Gloss
<b>Mode of Application</b>	Roller – brush- gun
<b>Storage</b>	2 years in proper condition

### Surface Preparation:

The surfaces should be dry, clean and free from contaminates such as grease, oil, dust, which can result in poor adhesion of the paint to the surface. Use a suitable solvent for cleaning old flaking paint or poorly bound surfaces must be removed completely.